



999.00 EUR
incl. 19% VAT, plus [shipping](#)

Experience high-performance and rock solid stability in a small form factor with the ZOTAC G41-ITX powered by the Intel® G41 Express chipset. The ZOTAC G41-ITX platform is designed to accept high-performance Intel® Core™ 2, Celeron® and Pentium® processors while occupying a miniscule amount of space thanks to the mini-ITX form factor.

Just because the ZOTAC G41-ITX is a mini-ITX platform doesn't mean it has limited capabilities. Packing one eSATA 3.0 Gb/s and four SATA 3.0 Gb/s ports, full-speed PCI Express x16, 802.11n WiFi and Gigabit LAN, the ZOTAC G41-ITX is proof you can have big system performance in a mini-ITX form factor.

Product Name

Product Name ZOTAC G41-ITX WIFI

Model

Model G41ITX-B-E

Chipset

Manufacturer Intel
Chipset G41 Express
GPU Intel® GMA X4500

CPU Compatibility

Name Intel® Core 2™ Duo
Intel® Core™ 2 Quad
Intel® Pentium®
Intel® Celeron®
Up to 65-watt TDP
Socket LGA775
Bus Up to 1333 MHz

Memory

Memory Type DDR3
Memory Speed 1066 MHz
Slots 2 x 240-pin DIMM
Capacity Up to 8GB

CPU and Memory Compatibility List

CPU and Memory Compatibility List see above

3D API

DirectX	DirectX® 10
OpenGL	OpenGL® 2.0

Expansion

Slots	1 x PCI Express x16 1 x mini PCI Express (occupied by WiFi module)
-------	---

Networking

Ethernet	10/100/1000Mbps
WiFi	802.11n/g/b

Audio

AN/Alog	6-ch HD
Digital	N/A

Ports

DVI	1 (HDCP)
HDMI	1
VGA	1 (w/Adapter)
SATA	3 (SATA 3.0 Gb/s)
eSATA	1 (SATA 3.0 Gb/s)
PATA	N/A
PS/2	1 (keyboard only)
Serial Port	Serial port header
USB Ports	8 x USB 2.0 (6 on back panel / 2 via pin headers)
FireWire Ports	N/A

Cooler

Cooler	Passive (no fan)
--------	------------------

Form Factor

Form Factor	mini-ITX
-------------	----------

OS Compatibility

Windows	Windows® Vista / 7 Premium ready
---------	----------------------------------

General

SLI Supported	No
Maximum Resolution	2048 x 1536

Other

Wake-On Support	Wake-on USB Wake-on-LAN
Overclocking features	Yes

Packaging

Package Contents	2 x SATA cables 1 x SATA power cable 1 x DVI-to-VGA adapter 1 x I/O backplate
Graphics Output	1 DVI / 1 HDMI / 1 VGA