



298.00 EUR

incl. 19% VAT, plus shipping

- · Open-Frame!
- LED Backlight!
- Auto Power On!

Support: Dimensions | 🔁 Dimensions (PDF)

New: LED-Backlight-Technology, with optimized color saturation enabling particular high and shining display. The scale of displayable color nuances is increased by 45% because of the new technology. Conventional LCDs are based on CCFL backlight, which can display approx. 72% of the standard color scale of NTSC (National Television Systems Committee). With LED-Backlight-Technology 104% of the NTSC-color scale can be displayed. This results in displaying in a highly realistic manner.

With the new Open-Frame TFT display-series from CarTFT you get back control: The ruggedized metal frame enables you a stable installation. The single modules (Mainboard, Touchscreen controller, Power inverter and button-frame) can be screwed off from the rear side and beeing positionated elsewhere. This way you can install the connector cables more easier and the display thickness shrinks also.

Note: This Open-Frame TFT display is an offer primarily meant for business and project customers. End consumers should only handle with unprotected electronic parts with appropriate experience.

Possible additional options (starting from a MOQ of 20 units):

- Speakers
- Different cable lengths



- Other display models/sizes
- Touchscreen RS232 instead of USB
- Other connector types
- [...] Ask us!

Additional informations:

With the touchscreen functionality you easily can control your PC. The briliant VGA-display ensures a maximum readability and sharpness.

AC-Adapter for home usage and a car cigarette lighter adapter are included.

The CTF-800ML can be used with any PC/MAC with VGA- and USB port.

Driver-CD included, compatible with:

- Windows 95/98/ME/NT4/2000/XP/7/8/8.1/10
- XP Tablet PC Edition
- Windows CE 2.12, 3.0, .net
- Linux RedHat, Mandrake,...
- Macintosh OS 9.x, 10.x
- DOS,..

8.0" digital
4:3 wide TFT screen
2400x600= 1,440,000 dots
800x600
640x480-1920x1080
RGB stripe
600 nits
500:1
30°C to 85°C
DC 9-30V
max. 10W
2x Video inputs (PAL/NTSC)
1x VGA input
185.6 x 143.6 x 27 mm
Display : 162 x 121.5 mm
1.0Vp-p, composite video
Full function OSD control (englisch)
Auto Power On/Off
LED backlight
Autodimmer
8.0" VGA Open-Frame Touchscreen TFT with Video-support
Power Adapter f. EU 230V
Cigarette Lighter Adapter
Touchscreen Driver-CD
- Manual